

I PRICE GROUP

KEIMO

KEIMO

surface 100% PU/basic material 85% polyester, 35% cotton, weight 435 g/m² +/-5%, abrasion >100 000 Martindale cycles (EN ISO 2470-2 method 1), light fastness >5(EN ISO 105-B 02), resistance to pilling 4-5 (EN ISO 105-X12), non-flammability certifiat (BS 5852/DIN EN 1021-1)



II PRICE GROUP

FIGHTER, PASTEL, VALENCIA, ERA, ROCCIA, CHARLES, CHARLES STUDIO DESIGN


FIGHTER

polyester 100%, weight 390 g/m², abrasion 130 000 cycles Martindale, resistance to pilling 4-5 (EN ISO 12945-2), light fastness >5 (EN ISO 105-B02), non-flammability certificate (BS EN 1021-1, BS EN 1021-2, BS 5852 part 10.1), Q1 UK, UNI 9179 Class 1 (EMME)



PASTEL

polyester 100% - TREVIRA CS, weight 250g/m² +/-5%, abrasion 80 000 Martindale cycles, resistance to pilling 5 (EN ISO 12945), light fastness 6 (EN ISO 105-B02), non-flammability certificate (EN 1021-1, EN 1021-2, Crib 5, BS 7176 Medium Hazard: C1, M1, E1, IMO A 652/16), IMO A 471(X)




VALENCIA

surface 100% vinyl/basic material - 100% polyester weight 850g/m², abrasion 300 000 Martindale cycles (UNE EN 14495:2004), non-flammability certificate (EN 1021-1, EN 1021-2, BS EN 1021-1/2; DIN EN 1021-1/2; IMO A 602/10) (S-2-S-3, FAR 25 853 (X) APF Part 10a) (1)(ii)), light fastness > 5 (EN ISO 105-B02) antimicrobial protection, antibacterial protection, antifungal protection, abrasion resistance, resistance to dirt(blood, urine)



ERA

Composition: Polyester 100%, Weight: 320g/m² +/-5%, Abrasion Resistance 100 000 Martindale cycles (EN ISO 12947:1098), Fastness to Rubbing 4 (ISO 105-X12:2002), Light Fastness 5 (EN ISO 105-B02:2014), Flammability (BS EN 1021-1 / BS EN 1021-2 / BS 7176:2007 Low Hazard)



ROCCIA

100% polyester-TREVIRA CE weight 250g/m² +/-5%, abrasion 70 000 Martindale cycles (UNI EN ISO 12947:2), resistance to pilling 5 (EN ISO 12945:2), light fastness 6 (EN ISO 105-B02), fastness to rubbing 4 (UNI EN ISO 105-X12) dry 5 (UNI EN ISO 105-X12), non-flammability certificate, EN 1021-1:2008 EN 1021-2:2008 BS 7176:2007 (Medium Hazard), BS 5852:2006 (Crib 5), NFP 90-501-1 (M1), DIN 4102-1 (B1), IMO Res. A 552 (16) Part 5 UNI 9174-UNI 8495 (C1), AM 18/VF D 80013) UNI 9170 Class 1 IM



CHARLES

Composition: 100% Polyester Weight: 290 g/m² Roll width: 140cm Abrasion Resistance 60.000 Martindale cycles (BS EN ISO 12947-2:1995) Pilling: 4 (EN ISO 12 945-2) Light Fastness 5 (ISO 105-B02) Fastness to Rubbing Ywe: 4-5 (UNI EN ISO 105-X12) Dry: 4-5 (UNI EN ISO 105-X12) Flammability: DIN EN 1021-1 Charles fabric, due to its structure (long hair), can be arranged in a velour way while being used, creating the impression of different shades of upholstery, it is also susceptible to bending while sitting, which is why it should be combed very gently.



CHARLES STUDIO DESIGN [#FAFA82](#) [#756C775D](#) [#D178A703](#)

Composition: 100% Polyester Weight: 290 g/m² Roll width: 140cm Abrasion Resistance 60.000 Martindale cycles (BS EN ISO 12947-2:1995) Pilling: 4 (EN ISO 12 945-2) Light Fastness 5 (ISO 105-B02) Fastness to Rubbing Ywe: 4-5 (UNI EN ISO 105-X12) Dry: 4-5 (UNI EN ISO 105-X12) Flammability: DIN EN 1021-1 Charles fabric, due to its structure (long hair), can be arranged in a velour way while being used, creating the impression of different shades of upholstery, it is also susceptible to bending while sitting, which is why it should be combed very gently. *Extended delivery time



III PRICE GROUP

AQUARIUS, BLAZER, SILVERTEX, CRISP, FAME, SYNERGY

AQUARIUS

wool 100%, weight 370 g/m² ± 5%, abrasion 60 000 Martindale cycles (BS 5000), resistance to pilling > 4, (BS EN ISO 12945-2:2000), light fastness 5 (ISO 105-B02:2013), non-flammability certificate (BS EN 1021-1, BS EN 1021-2, BS 7176:2007 Low Hazard) Fabric available until 31.12.2018



BLAZER

virgin wool 100%, Weight 450g/m² ±5%, abrasion resistance 50 000 Martindale cycles, fastness to pilling 4 (BS EN ISO 12945-2:2000), light fastness 5 (ISO 105-B02:1996), non-flammability certificate, BS EN 1021-1:2006, BS EN 1021-2:2006, BS 7176:2007 Low Hazard Fabric available until the end of the year



SILVERTEX

surface-100% Vinyl basic material - 100% Polyester H-LcR2, weight 665g/m², abrasion 300 000 Martindale cycles (EN ISO 12947:1999 Part 2), light fastness >7, non-flammability certificate (BS EN 1021-1:2, EN 1021:2, EN 71-2, IMO A 652(10) 2-8.3, FMVSS302)



CRISP

85% wool, 7% polyamide weight: 328 g/m² abrasion: 200000 Martindale cycles (EN ISO 12947-2) resistance to pilling 4-5 (EN ISO 12945-2) light fastness 5-7 (EN ISO 105-B02) rubbing fastness 4-5 (EN ISO 105x12 (wet/dry)) non-flammability certificate, EN 1021-1,2, BS 5852 06:1, Calif. Bul. 117-E class 1, IMO MS c307(88) Annex 1 part 6, MED certificate IMO



FAME

85% wool, 5% polyamide weight: 450 g/m² abrasion: 200 000 Martindale cycles (EN ISO 12947-2) resistance to pilling 4 (EN ISO 12945-2) light fastness: 5-7 (EN ISO 105-B02) rubbing fastness: 4-5 (EN ISO 105x12 (wet/dry)) non-flammability certificate, EN 1021-1,2, BS 5852:2006 (Crib 5), BS 5852 06:1, UNI 9175 class 1 IM, Calif Bul. 117-E class 1 cleaning: dry cleaning



SYNERGY

Composition: virgin wool 90%, polyamide 5%, Weight: 400g/m² ±5% Abrasion Resistance > 100 000 Martindale cycles, Fastness to Rubbing: 4 (ISO 105-X12) Light Fastness: 5 (ISO 105-B02) Flammability: EN 1021-1&2 Cigarette & Match NF C 60-013 UNI 9175 Classe 1 IM BS 7176 Low Hazard



IV PRICE GROUP

REMIX, LEATHER, REMIX STUDIO DESIGN


REMIX

Composition: 90% wool, 10% nylon Weight: ok. 300 g/m² Abrasion Resistance: 100 000 Martindale cycles, Pilling: 3-4 (EN ISO 12045-2:2000) Light Fastness: 5-7 (ISO 105-B02:2000) Flammability: EN 1021 - 1/2 BS 5852 Part 1 Chrom B11Q1 UNI 9175 (MO A.662)16) Cr6 B and B2 Producer: Kvadrat Denmark



LEATHER

size: Ca. 5x12, thickness >0.8mm-1, 1mm, wet rub tests >250 (BS EN ISO 11840, 1996) dry rub tests >500 (EN ISO 11540:1996) flex resistance > 50 000 cycles (BS EN ISO 5402:2002), PCP and CPC used during tanning process, natural colour variations may occur, non-flammability certificate (EN ISO 1021-1:2006, UNE EN 1021-2:2006)



REMIX STUDIO DESIGN AVAILABLE AT SELECTED DISTRIBUTORS

Composition: 90% wool, 10% nylon Weight: ok. 300 g/m² Abrasion Resistance: 100 000 Martindale cycles, Pilling: 3-4 (EN ISO 12045-2:2000) Light Fastness: 5-7 (ISO 105-B02:2000) Flammability: EN 1021 - 1/2 BS 5852 Part 1 Chrom B11Q1 UNI 9175 (MO A.662)16) Cr6 B and B2 Producer: Kvadrat Denmark *Extended delivery time



*Delivery term for orders for Studio Design fabrics is up to 4 weeks.

METAL

METAL

METAL

colors frames



WOOD

WOOD

WOOD

-



V PRICE GROUP - STUDIO DESIGN

STEELCUT TRIO 2, TURNBERRY, TROON, ACCESSOIRE

STEELCUT TRIO 2 STUDIO DESIGN

Composition: 90% wool, 10% nylon; Abrasion Resistance 100 000 Martindale cycles; Fastness to Rubbing 5-4 (EN ISO 12045); Light Fastness 5-7 (ISO 105-B02); Flammability: EN 1021-1/2; BS 5852 part 1; DIN 4102 B2; Chrom B11Q1; NF D 60 013; UNI 9175 11M; US Cal. Bul. 117, - 2013; IMO FTP Code 2010; Part 6




TURNBERRY **STUDIO DESIGN**

Composition: 100% wool, Weight: 586 g/m² ± 5%; Abrasion Resistance: 43 000 cycle Martindale; Flammability: BS EN 1021 - 1; CRIB 5



ROON **STUDIO DESIGN**

Composition 92% wool, 7% nylon; Weight: 37 g/m² ± 5%; Abrasion Resistance: 60 000 cycle Martindale; Flammability: BS EN 1021 - 1; CRIB 5



ACCESSOIRE **STUDIO DESIGN**

Composition: 85% wool 15% polyamide, Weight: 350 g/m² ± 5%, Abrasion Resistance 50 000 Martindale cycles; Fastness to Rubbing: 4 (EN ISO 105-C06); Light Fastness: 5-7 (EN ISO 105-B02); Flammability: BS EN 1021-1 BS EN 1021 - 2

