

Materials and colours

Upholstery

MESH IR

MESH RR

MESH RY | RHYTHM

MESH SH

Mesh. Composition: 100% Polyester. Weight: 360 g/m². Abrasion resistance: 100.000 cycles DIN EN ISO 12947-1-2/00. Fastness to light: DIN EN ISO 105 - B02:5. Fastness to rubbing: DIN EN ISO 105-X12:5.

It is washable with lukewarm water (max 30°C) and mild soap; do not use harsh cleaning agents neither solvents or products derived from oil.



Please refer to the Price list in force and to the General sale conditions for the colours and the combinations available for every single product.

Colours shown are used for reference only and may look different in reality. Please contact SitLand to receive more informations.

Materials and colours

Upholstery

MESH IR

MESH RR

MESH RY | RHYTHM

MESH SH

Mesh fabric made of 100% Polyester, STRETCH. Eco-friendly Fabric Oeko-Tex 100 certified. The dyes are 100% free of heavy metals. Weight: 318 g/m² Abrasion Resistance: 70.000-80.000 Martindale cycles EN ISO 12947-2 Flammability: EN 1021- 1&2. UNI 9175 Class 1. California Bull. 117E. Color fastness to light: ISO 105-B02:5 Color fastness to rubbing: EN ISO 105x12:4/5 (dry/wet). Pilling EN ISO 12945-2: 5.

Hoover with a vacuum cleaner at least once a month, taking care do not to rub on the surface of the fabric. Washable at 40°C by hand; max shrinkage of 5%. Small spots and/or stains can be cleaned with a damp cloth and a very small amount of mild soap. Allow to dry naturally, do not rub. Do not use cleaning agents that contain alcohol and/or ammonia or harsh detergents that can damage the appearance and the tightness of the fabric over time. The RR fabric has a ten-year guarantee against wear-through in normal office or home use.

Please refer to the Price list in force and to the General sale conditions for the colours and the combinations available for every single product.

Colours shown are used for reference only and may look different in reality. Please contact SitLand to receive more informations.



Materials and colours

Upholstery


- MESH IR
- MESH RR
- MESH RY | RHYTHM
- MESH SH

RY | Rhythm by Gabriel
Designer: Gabriel Design Team

Composition: 100% Polyester flame retardant. Weight: 525 g/lm. Flammability: BS EN 1021-1 cigarette, BS EN 1021-2 Match, BS 5852 Part 1 0, 1 Cigarette & match, BS 5852 Crib 5, BS 7176 Medium hazard, DIN 4102 B1, NF P 92-503 M3, UNI 9174 Classe Uno - UNI 8457, US California Technical Bulletin 117-2013. Abrasion: EN ISO 12947-2:70.000 Martindale cycles. Pilling: EN ISO 12945-2: 5. Colour fastness to light: EN ISO 105-B02: 5-7. Colour fastness to rubbing: EN ISO 105x12 (wet/dry): 4-5. Colour: slight difference may occur. Environment: Oeko Tex, 100% free of heavy metals. US Act: AATCC 16 Colour fastness to light; AATCC 8 or 116 Wet/dry crocking; AATCC 15 Perspiration; ASTM D3511 Pilling; ASTM D4034 Yarn slippage at a sewn seam; ASTM D5034 Breaking force; ASTM D4157-07 Wyz abrasion (heavy duty); CA TB 117-2013. Vacuum clean regularly; small spots and/or stains can be cleaned with a damp cloth and a very small amount of mild soap. Allow to dry naturally, do not rub. Do not use cleaning agents that contain alcohol and/or ammoniac or aggressive detergents that can damage the appearance and the tightness of the mesh fabric over time.

Please refer to the Price list in force and to the General sale conditions for the colours and the combinations available for every single product.

Colours shown are used for reference only and may look different in reality. Please contact SitLand to receive more informations.



Materials and colours

Upholstery

MESH IR

MESH RR

MESH RY | RHYTHM

MESH SH

Mesh. Composition: 81% Polyester 18% Polyamide 1% Elastan. Weight:400 g/m².
Abrasion Resistance: 30.000 cycles Martindale DIN EN ISO 12947-2. Flammability:
D- DIN EN 1021 part 1 (cigarette test) tested on flammable foam B3 density equal to
22 kg/m³ minimum classification of flammability of assembly (simulation padding)
according to DIN 66084 P-c. Fastness to light: DIN EN ISO 105 - B02:5-7. Fastness
to rubbing: DIN EN ISO 105-X12:4-5 dry and wet. Fastness to sweat: DIN ES ISO
105-E04:4-5 acid and alkaline.

For the cleaning of fixed slipcovers: vacuum regularly, being careful no to rub the
fabric.

Please refer to the Price list in force and to the General sale conditions for the
colours and the combinations available for every single product.

Colours shown are used for reference only and may look different in reality. Please
contact SitLand to receive more informations.

